

GHG Analyzer Travels Anywhere



Ultraportable Greenhouse Gas Analyzer (CH_4 , CO_2 , H_2O)

Features and Benefits

- 17 kg, 70 watts
- Gases measured simultaneously
- All spectra always viewable
- CH_4 and CO_2 reported on dry mole basis directly
- Ideal for chamber flux, soil studies, emissions compliance monitoring, leak detection
- Wide measurement range
- New *Extended Range* option allows methane measurements at levels up to 10%
- Species specific - no cross interferences
- Operates directly on DC power

LGR's new Ultra-Portable Greenhouse Gas Analyzer (UGGA) reports measurements of methane, carbon dioxide and water vapor simultaneously in a package that is compact, crushproof and travels anywhere. Small enough to be carried on-board aircraft (TSA approved size) and requiring less than 70 watts, the UGGA offers opportunities to measure GHG anywhere. As with all LGR instruments, the UGGA is simple to use which makes it ideal for field studies, compliance monitoring, leak detection, air quality studies and soil flux studies, and wherever measurements of methane, carbon dioxide and water vapor are needed.

In addition, the UGGA reports and stores all measured absorption spectra which allows the instrument to accurately correct for water vapor dilution and absorption line broadening effects and thus to report CH_4 and CO_2 on a dry mole fraction basis without drying or post processing. Furthermore, LGR's "*Extended Range*" option provides accurate methane measurements at levels up to 10% mole fraction (without dilution) without reducing precision and sensitivity at

typical ambient levels - a unique capability to LGR. Moreover, only LGR's analyzers provide reliable *guaranteed* measurements at mole fractions greater than 100 times ambient levels.

LGR's patented technology, a fourth-generation cavity enhanced absorption technique, has many advantages (simpler, easier to build, rugged) over older, conventional cavity ringdown spectroscopy (CRDS) and direct absorption techniques. As a result, LGR Analyzers provide higher performance at lower cost.

LGR Analyzers have an internal computer (Linux OS) that can store data practically indefinitely on a hard disk drive and send real time data to a data logger via the digital (RS232), analog or Ethernet outputs. In addition, LGR analyzers may be controlled remotely via the Internet. This capability allows the user to operate the analyzer using a web browser anywhere. Furthermore, remote access allows full control of the instrument and provides the opportunity to obtain data and diagnose the instrument operation without being on site.

Ultraportable Greenhouse Gas Analyzer (CH₄, CO₂, H₂O)

Performance Specifications

Repeatability / Precision (1-sigma):

CH₄: <2 ppb (1 sec), <0.6 ppb (10 sec),
<0.25 ppb (100 sec)

CO₂: <300 ppb (1 sec), <100 ppb (10 sec),
<40 ppb (100 sec)

H₂O: <100 ppm (1 sec), <35 ppm (10 sec),
<15 ppm (100 sec)

Response Time (flow time through meas. cell):
10 s

Measurement Range:

CH₄: 0.01 – 100 ppm
CO₂: 1 – 20000 ppm
H₂O: 500 – 70000 ppm

Operational Range:

CH₄: 0 – 500 ppm
CH₄: 0 – 10% (with Extended Range option)
CO₂: 0 – 20000 ppm
H₂O: 0 – 70000 ppm

Outputs:

Digital (RS232), Analog, Ethernet, USB

Data Storage:

Internal Solid State Hard Disk Drive

Ambient Humidity:

<98% RH non-condensing

Operating Temperature:

5 – 45 °C

Inlet / Outlet Fittings:

1/4" Push-Connect

Power Requirements:

60 watts (10-30 VDC)
66 watts (115/230 VAC, 50/60 Hz)

Dimensions:

7" H x 18.5" W x 14" D

Weight:

17 kg



Ordering Information

U-GGA-915: Ultraportable, GLA132 Series

OPT-EXTENDED-CH4 - extends measurement range to LEL
of methane (5% / 50,000ppm)

Accessories (optional)

MIU-16: Multiport Inlet Unit – 16 inlet port multiplexer

MIU-8: Multiport Inlet Unit – 8 inlet port multiplexer

OPT-DATALOG: Data Logging System – multi-channel data
logging sys-tem records and synchronizes serial (RS-232) outputs
from multiple LGR analyzers and other devices (GPS,
anemometers)

UK & Ireland Distributor