



CuraTerra THC-CH₄-NMHC Analyzer

Model N901



- ▶ Fast Response
- ▶ Low Detection Limit
- ▶ Intuitive User Interface
- ▶ Sample Particulate Filter
- ▶ Automatic Baseline
- ▶ Dedicated Graphical Calibration Screen
- ▶ Internal AutoCal Valve Option

N Series Platform Features



Color Touch-Screen
Graphics Display



Two Front Panel USB Ports



Modular Internal Hardware
Design



All DC-powered Internal
Components



Large Internal Data Storage



Serial and TCP/IP Ethernet
Included



Digital and Analog
Expansion Options



Indicator Illuminated Soft
Power Switch

The Model N901 is a near-continuous hydrocarbon gas analyzer that measures the concentration of Methane (CH₄) and Total Hydrocarbons (THC) in air. The concentration of the non-Methane (NMHC) component is calculated by the subtraction of CH₄ from THC, with high sensitivity and accuracy. The hydrocarbons are measured using a Flame Ionization Detector (FID), in combination with gas chromatography (GC). The instruments range and performance are tuned specifically for use in ambient air quality monitoring assessments.

The Model N901 is designed for simple operation and maintenance with a modular hardware and electronics architecture. A long-life stainless-steel fritted filter is used at the sample intake to effectively remove particulate matter without introducing any gas-phase measurement artifacts. Instrument operation, calibration functions, chromatogram views, and data handling are all automated and controlled using the internal NumaView™ Software (NVS) interface, without the need for an external PC.

For remote connection to the N901 instrument, Teledyne API's NumaView™ Remote PC-based Software provides a virtual interface, instrument controls, and data downloading capability to all TAPI analyzers operating NumaView™ Software.



N901 Specifications

• Detector	Flame Ionization Detector (FID)
• Method	Gas Chromatography with CH ₄ separation column
• Ranges (Methane)	Min: 0-5 ppm Max: 0-1,000 ppm
• Lower Detectable Limit	<25 ppb (Methane); <25 ppb (Propane)
• Cycle Time	60 sec (minimum), user-definable
• Precision	<1% of reading or 0.05 ppm (whichever is greater)
• Linearity	<1% of full scale
• Zero Drift	Zero baseline performed once per cycle
• Span Drift (24hr)	<1% of full scale
• Sample Flow Rate	60 cc/min $\pm$ 10%
• Carrier Gas	50 to 70 psi, N2 UHP Grade, Consumption 20 cc/min
• Fuel Gas	50 psi $\pm$ 5%, H2 UHP Grade, Consumption 35 cc/min
• FID Air	50 psi $\pm$ 5%, HC Free clean air, Consumption 350 cc/min
• Auxiliary Air	70 psi $\pm$ 5%, Clean Dry Air, Consumption 1 cc/actuation
• Included I/O	1 x Ethernet (TCP/IP) 1 x RS232 2 x front panel USB device ports
• Optional I/O	Universal Analog Output Board includes (all user-definable): 4 x Isolated Voltage Outputs (5V, 10V; user-selectable) 3 x Individually Isolated Current Outputs (4-20mA) Digital I/O Expansion Board includes: 3 x Isolated Digital Input Controls 5 x Isolated Digital Output Controls (user-definable) 3 x Form C Relay Alarm Outputs (user-definable)
• Weight	35 lbs (16 kg)
• Dimensions (HxWxD)	7" x 17" x 23.5" (178 x 432 x 597 mm)
• Operating Temperature	5-40°C
• Power	100-240V, 50/60Hz, Typical Power 130W

*Specifications subject to change without notice.
All specifications are based on constant conditions.*